



KENWORTH
THE WORLD'S BEST

PRIMAAX[®] EX

HENDRICKSON
The World Rides On Us[®]

PRIMAAX® EX — MAAXIMIZE PERFORMANCE AND DURABILITY

PRIMAAX® EX is a severe-duty vocational air suspension designed specifically for the rigorous demands of vocational, severe service and heavy haul applications. The system provides technologically advanced features designed to enhance durability, reliability, and handling characteristics.

Genuine Hendrickson Torque Rods

- Optimized configuration helps improve handling and roll stiffness for expanded applications
- Premium retained rubber bushings for increased service life and resistance to walkout
- Alternative rods available for disc brake use

QUIK-ALIGN®

- Allows for easy axle alignment without shims
- Reduces maintenance time and helps extend tire life

Axle Connections

- D-pin axle connection decreases torsional axle stress for reduced maintenance and improved joint integrity
- Integrated axle stop contact pads reduce axle stress

Air Springs

- Large volume, low frequency design for improved ride
- Advanced design air springs provide fast fill time

Structural Beams

- Integrate end caps for increased reliability
- Utilize premium materials for high durability
- Robust rubber bushings improve service life and eliminate lubrication requirements

Height Control Valve

- Maintains proper suspension ride height
- Twin height control valves available for improved leveling in applications with uneven loading

Heavy-duty Shock Absorbers

- Positioned and tuned for optimum damping characteristics

Cross Beams

- Seamless fabrication technology forms a robust torsion system with structural beams, improving stability

	PAX EX 232T	PAX EX 262T	PAX EX 262S	PAX EX 462	PAX EX 522	PAX EX 692
Axle Configuration	Single	Single	Single	Tandem	Tandem	Tridem
Site Travel Rating	30,000 lbs.	33,000 lbs.	33,000 lbs.	60,000 lbs.	66,000 lbs.	90,000 lbs.
Axle Travel	8 in.	8 in.	7 in.	8 in.	8 in.	8 in.
Ground Clearance	10.75 in.	10.75 in.	9.0 in.	10.75 in.	10.5 in.	10.75 in.
Ride Heights	15.5 in.	15.5 in.	8.5 in.	10 in.	10 in.	10 in.
Axle Spacing	N/A	N/A	N/A	52 - 72.5 in.	54 - 72.5 in.	52 - 60 in.

Visit www.hendrickson-intl.com for additional information.

Note: Photography and illustrations in this brochure may depict optional equipment. All equipment and specifications shown in this brochure are subject to change without notice. Please consult with your Kenworth dealer at the time of ordering for actual standard and optional equipment.



A **PACCAR** COMPANY

KENWORTH TRUCK COMPANY

P.O. Box 1000

Kirkland, Washington 98083-1000

(425) 828-5000

CANADIAN KENWORTH COMPANY

6711 Mississauga Road N.

Mississauga, Ontario L5N 4J8

(905) 858-7000