

- Trusted name
- Superior axle design
- Application versatility

**Trusted Name**

Worldwide OEMs, fleets and owner operators put their trust in INTRAAX®. With a well-deserved reputation for low maintenance and durability, AAL models deliver the proven benefits of INTRAAX technology to trailer designs for low-ride height or liftable suspensions.

Superior Axle Design

Hendrickson's INTRAAX AAL product line now features the 5¾-inch LDA™ Large-Diameter Axle. The road-proven LDA axle reduces weight, improves performance, increases axle stiffness and improves durability.

Application Versatility

The sleek, low-profile design of AAL models cover a wide range of ride heights from low-deck trailers to high-clearance off-highway operations. The exceptional axle travel of this system also makes the AAL an ideal liftable suspension. Teamed with our UBL™ UNDER BEAM LIFT™, this lift axle combo provides excellent ground clearance when raised.

To learn more about INTRAAX AAL, call 866.743.3247 or visit www.hendrickson-intl.com

INTRAAX® AAL Features and Benefits

TRI-FUNCTIONAL® Bushing

- Rigid trailing arm and solid axle connection for optimum ride softness and stability

Standard Trailer Cam Tube System™

- Enhances S-cam alignment and helps extend life of brake components
- Short 10-inch S-cam reduces windup and bushing wear for responsive, consistent stopping power

Brake Component Mounting

- Welded to trailing arms rather than axle; minimizes axle stress

Neutral-toe Axle

- Helps increase fuel economy and tire life
- Straight tracking

LDA™ Large-Diameter Axle

- Trims weight compared to 5-inch axle, allowing more cargo per load
- Bending and torsional stiffness increased for rugged durability
- Greater roll stability
- Reduced deflection under load

QUIK-ALIGN® Pivot Connection

- Fast and easy axle alignment
- Requires no welding or special tools

Advanced Axle Wrap and Window Weld

- Provides optimal structural integrity



Value-Added Options

- RTR® READY-TO-ROLL® wheel-end options reduce weight, enhance durability and lower maintenance
 - **HXL3® Hendrickson Extended-Life 3-year System™** features a three-year limited on-highway warranty*
 - **HXL5® Hendrickson Extended-Life 5-year System™** features a five-year limited on-highway warranty*
 - **HXL7® Hendrickson Extended-Life 7-year System™** features a seven-year limited on-highway warranty*
- TIREMAAX® tire inflation system helps maximize tire life and maintain peak fuel mileage
- HXS® Hendrickson Extended Service™ brakes extend intervals between brake service
- UBL™ UNDER BEAM LIFT™ is a lightweight mechanism which offers cost savings and operational flexibility
- Rear shock options available
- Air disc brakes available (requires rear shock option)

See RTR READY-TO-ROLL Wheel-End flyer - Literature No. L1200

See Raised-Center Axle Flyer - Literature No. L1065

See TIREMAAX PRO Brochure - Literature No. L1199

See UBL UNDER BEAM LIFT Flyer - Literature No. L727

*Contact your local Hendrickson representative for complete warranty terms, conditions and limitations.

Specifications

MODEL	MAXIMUM CAPACITY (lbs.)	AXLE RATING ¹ (lbs.)	AXLE DIAMETER	RIDE HEIGHTS (Inches)	APPLICATION WEIGHT (lbs.)
AAL 23K	23,000	23,000	LDA™	6.5, 7.5, 8, 9, 12, 14, 15, 16, 17, 19	570
AAL 25K	25,000	25,000	LDA	6.5, 7.5, 8, 9, 12, 14, 15, 16, 17, 19	586
AAL 30K	30,000	25,000	LDA	9, 12, 14, 15, 16, 17, 19	612

¹Axle structure rating only. Brakes rated separately.

Actual product performance may vary depending upon vehicle configuration, operation, service and other factors.

All applications must comply with applicable Hendrickson specifications and must be approved by the respective vehicle manufacturer with the vehicle in its original, as-built configuration.

Contact Hendrickson for additional details regarding specifications, applications, capacities, and operation, service and maintenance instructions.

Call Hendrickson at **330.489.0045** or **866.RIDEAIR (743.3247)** for additional information.



www.hendrickson-intl.com

TRAILER COMMERCIAL VEHICLE SYSTEMS

2070 Industrial Place SE
Canton, OH 44707-2641 USA
866.RIDEAIR (743.3247)
330.489.0045 • Fax 800.696.4416

Hendrickson Canada

250 Chrysler Drive, Unit #3
Brampton, ON Canada L6S 6B6
800.668.5360
905.789.1030 • Fax 905.789.1033

Hendrickson Mexicana

Circuito El Marqués Sur #29
Parque Industrial El Marqués
Pob. El Colorado, Municipio El Marqués,
Querétaro, México C.P. 76246
+52 (442) 296.3600 • Fax +52 (442) 296.3601

L1066 Rev F 05-19

© 2008 – 2019 Hendrickson USA, L.L.C. All Rights Reserved. All trademarks shown are owned by Hendrickson USA, L.L.C., or one of its affiliates, in one or more countries.

Information contained in this literature was accurate at the time of publication. Product changes may have been made after the copyright date that are not reflected.

Printed in United States of America