

H COMFORT AIR[®] Single axle air suspension for Hino vehicles



- Superior comfort
- Outstanding ride
- Improved handling
- Reduced maintenance



To learn more about COMFORT AIR[®],
call 855.743.3733 or visit
www.hendrickson-intl.com

H HENDRICKSON
The World Rides On Us[®]

19,000 - 23,000 lb. capacity COMFORT AIR® for Hino Vehicles

Reduced Maintenance

- Wide footprint of frame hanger bracket distributes load over a larger area, reducing stress to the frame to help increase the life of the vehicle
- Durable pivot bushing connection provides quiet operation and helps extend suspension service life

Height Control Valve

- Fast acting HCV maintains precise ride height control through changing road surfaces, loads and driving conditions

Stability and Handling

- Durable ULTRA-ROD® enhances handling during cornering by controlling lateral forces to maintain axle position

QUIK-ALIGN®

- Reduces maintenance time by offering a fast and easy method to adjust and set alignment without shims

21k and 23k Capacities
(21k pictured)

Shock Absorbers

- Tuned for optimum dampening characteristics to provide maximum driving comfort

Main Support Member

- Extended length generates lower spring rate for optimized roll stiffness, providing a more comfortable and compliant ride

Air Springs

- Adjust to changing load conditions to deliver superior ride quality

	CA190	CA210	CA230
Suspension Capacity	19,000 lbs.	21,000 lbs.	23,000 lbs.
Suspension Weight	460.5 lbs.	461 lbs.	530 lbs.
Main Support Member	Single	Single	Double

All applications must comply with applicable Hendrickson specifications and must be approved by Hino with the vehicle in its original, as-built configuration.
All marks are trademarks of their respective owners.

Call your Hino truck dealer or Hendrickson at **630.910.2800** or **855.RIDERED (743.3733)** for additional information.



TRUCK COMMERCIAL VEHICLE SYSTEMS
800 South Frontage Road
Woodridge, IL 60517-4904 USA
855.RIDERED (743.3733)
630.910.2800 • Fax 630.910.2899

www.hendrickson-intl.com



www.hino.com