

OPTIMIZE fuel economy and weight savings with Hendrickson's versatile OPTIMAAX<sup>®</sup> 6×2 suspension system



Hendrickson's OPTIMAAX<sup>®</sup> system is a revolutionary 6×2 solution to help fleets save fuel cost, tire wear and weight with comparable handling to 6×4 tandem axle configurations. Operating as a liftable axle in the forward tandem position, this system provides versatility for fleets with variable loads. The OPTIMAAX system is ideal for fleets in need of additional flexibility for on-highway tractor applications.

To learn more about OPTIMAAX,  
call 855.743.3733 or visit  
[www.hendrickson-intl.com](http://www.hendrickson-intl.com)

**H HENDRICKSON**  
*The World Rides On Us<sup>®</sup>*

# OPTIMAAX® System Features and Benefits

- **OPTIMIZE Automated Controls**

*Proprietary program logic controls lift axle movement, load transfer and braking functions*

- Fully automated controls eliminates driver intervention and training
- Automates axle lowering and lifting by sensing load capacities

- **OPTIMIZE Savings**

*Axle configuration saves up to 350 pounds and can help improve fuel economy up to 5 percent\**

- In general, 6×2 suspension systems for tractors can provide up to 3.5 percent decrease in fuel consumption compared to similar 6×4 tractors▲
- OPTIMAAX 6×2 system can provide up to 2.3 percent additional fuel consumption savings through lifting the non-drive axle▲▲
- Lifted axle saves on tire wear reducing tire maintenance costs

*\* Compared to 6×4 tandem axle configurations.*

- **OPTIMIZE Traction and Handling**

*Lifted axle position provides increased traction by increasing drive axle load*

- Improved traction when backing under trailers in soft soil or wet conditions versus traditional 6×2
- Maintains vehicle handling characteristics by keeping the drive axle behind the fifth wheel

## OPTIMAAX

- Ideal for diminishing load carriers such as: bulk haulers, grocery, livestock, beverage or applications experiencing empty back hauls
- Includes integrated lift axle, suspension and automated controls
- Available in 20,000 pound capacity
- Compatible with drum brakes

▲ Based upon testing conducted by Performance Innovation Transport (PIT) Group of FPIInnovations (2013).

Reference PIT Test Report: **Comparison of Fuel Efficiency and Traction Performances of 6×4 and 6×2 Tractors**

▲▲ Based upon independent proving grounds testing commissioned by Hendrickson



Axle lowered for 6×2 configuration — The OPTIMAAX system senses higher load conditions and lowers the non-drive axle



Axle lifted for 4×2 configuration — The OPTIMAAX system senses lighter load conditions and lifts the non-drive axle

*Actual product performance may vary depending upon vehicle configuration, operation, service and other factors.*

*All applications must comply with applicable Hendrickson specifications and must be approved by the respective vehicle manufacturer with the vehicle in its original, as-built configuration. Contact Hendrickson for additional details regarding specifications, applications, capacities, and operation, service and maintenance instructions.*

Call Hendrickson at **630.910.2800** or **855.RIDERED (743.3733)** for additional information.



[www.hendrickson-intl.com](http://www.hendrickson-intl.com)

#### TRUCK COMMERCIAL VEHICLE SYSTEMS

800 South Frontage Road  
Woodridge, IL 60517-4904 USA  
855.RIDERED (743.3733)  
630.910.2800 • Fax 630.910.2899

45745-401 Rev C 03-19

© 2014 - 2019 Hendrickson USA, L.L.C. All Rights Reserved. All trademarks shown are owned by Hendrickson USA, L.L.C., or one of its affiliates, in one or more countries.

Information contained in this literature was accurate at the time of publication. Product changes may have been made after the copyright date that are not reflected.

Printed in United States of America