

# INTRAAX® AAEDT 30K / AAEDL 30K ECHELLE DE CHARGE D'AIR / PSI

<b>Pression requis</b>	<b>Charge par essieux (Livres) lbs</b>	<b>Charge par essieux (Kilogrammes) kg</b>
<b>89</b>	<b>30,000</b>	<b>13,608</b>
<b>83</b>	<b>28,000</b>	<b>12,701</b>
<b>76</b>	<b>26,000</b>	<b>11,793</b>
<b>70</b>	<b>24,000</b>	<b>10,886</b>
<b>64</b>	<b>22,000</b>	<b>9,979</b>
<b>58</b>	<b>20,000</b>	<b>9,072</b>
<b>52</b>	<b>18,000</b>	<b>8,165</b>
<b>45</b>	<b>16,000</b>	<b>7,257</b>
<b>39</b>	<b>14,000</b>	<b>6,350</b>
<b>33</b>	<b>12,000</b>	<b>5,443</b>
<b>27</b>	<b>10,000</b>	<b>4,536</b>
<b>20</b>	<b>8,000</b>	<b>3,629</b>
<b>14</b>	<b>6,000</b>	<b>2,722</b>
<b>8</b>	<b>4,000</b>	<b>1,814</b>

Pour le numéro de pièce de ressort pneumatique: C-24445, C-24446, C-25319

**Trailer Commercial  
Vehicle Systems**

2070 Industrial Place SE  
Canton, OH 44707-2641 USA  
866.(RIDEAIR) 743.3247  
330.489.0045  
Fax 800.696.4416



[www.hendrickson-intl.com](http://www.hendrickson-intl.com)

**Hendrickson Canada**

250 Chrysler Drive, Unit #3  
Brampton, ON L6S 6B6 Canada  
800.668.5360  
905.789.1030  
Fax 905.789.1033

# Decal Specifications

Use this form to provide decal specifications, instructions for printer, application and/or other applicable information relative to printing or applying the decal.

The type of material and adhesive (except where specified) used to produce and apply a decal is determined by the printer according to the information listed on this page of the decal PDF file. Enter data in the fields below and in Table 1 as applicable.

ACTUAL SIZE: 4.00 W x 5.00 H Standard load scale decal size. See page 3 for typical placement.

Mounting Surface: Stainless steel or polycarbonate enclosure, inside (recommended) or outside.

Special Instructions: Although these decals are intended to be placed as shown on page 3, An OE or fleet may place them differently as desired.

Width Constraint 1	Height Constraint 1	Sunlight Exposure 2	Water Resistant 3	Water Proof 4	Special Adhesive 5	Paint Mask 6	Expected surface temp Max 7	Expected surface temp Min 8	Rounded Corners 9	Exposed to extreme Wind 10	Writable decal surface 11
4.30	5.40	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	140°F	-20°F	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

1. Relative to intended location, maximum or minimum size constraints must apply as listed. None if left blank.
2. Must not fade when exposed to sunlight for a minimum of 5 years.
3. Be able to resist rain water and hold position. Usually mounted vertically or at an incline such that water easily runs off.
4. Able to hold position and not degrade when submersed or held in standing water.
5. Applies to soft or hot wax coated suspension components and where ever applicable, when checked. X = adhesive specified in Table 2.
6. Covered with a removable mask. The mask should include a pull tab for ease of removal after painting.
7. Hold position and not fade or degrade when surface temperatures are as high as HHH° (enter value).
8. Hold position when surface temperatures are as low as -LLL° (enter value).
9. Rounded corners are used to resist wind which can lift sharp corners and eventually remove or damage decal.
10. An example of this would be a hubcap decal that is exposed to spinning and exposure to the wind and any particles carried within it.
11. Must be able to write on decal with permanent marker or ball point pen.

Table 1: Decal specifications

## SPECIAL ADHESIVES

The following are preferred adhesives for Hendrickson Trailer decals to be attached to soft coated suspension structural components. They have been tested with favorable results in Hendrickson Trailer applications. Hendrickson must be contacted prior to using other adhesive types in these applications.

Property	Fasson® TL2	
Manufacture	Fasson	
Manufacture web site	www.na.fasson.com	
Adhesive type	Hot melt rubber	
Minimum application temperature	35° F (2° C)	
Service temperature range	-65° F to 150° F (-54°C to 65.5° C)	

Table 2: Hendrickson approved decal adhesives

